

TECHNICAL DATASHEET MO23205

Ref. MO23205

Non Reusable





FFP2 NR D



The +

Electrostatic filter media
Sliding elastic band: better adjustment
Latex free to prevent the risk of irritation
Exhalation valve: reduction of breathing
resistance and avoid fog inside the mask

PURCHASE PACKAGING

 Ref.
 Size
 Inner
 Carton

 23205
 12

SALES PACKAGING



Individual pack

DESCRIPTION

Foldable half-mask in nonwoven polypropylene with exhalation valve, latex free synthetic rubber, adjustable nose clip

SECTORS

Heavy & process industries

Chemical & pharmaceutical industries

Light Industries

Infrastructure, building industry

Construction - finishing work

DIY

APPLICATIONS

For occasional use in a very dusty environment. Protections against non-toxic solid and liquid aerosols, such as calcium carbonate, kaolin, cement, cellulose, sulfur, cotton, flour, coal, ferrous metals, vegetable oils and tender woods.

Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods excepted).

Main risk

coverguard

TECHNICAL FEATURES

Features Foldable half-mask in non-woven polypropylen

SMS with valve

Latex free synthetic rubber

Adjustable nose clip

Other features welded outer contour ffp2 polypropylene sms

Weight 17g

Shape Flat foldable half mask with valve

Specifications FFP2 NR D

Harness features Synthetic elastic rubber (latex free)

Respiratory protection from aerosols and low

toxic dust

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **697918**Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands

EPI CAT. III

EN149:2001 + A1:2009

FFP2 NR D

Particle filtering half masks

RETAILER STAMP

MAJ 24/03/2022