

Lanyards



Absorbing Lanyards



The +

Elastic webbing reduces length when not in tension and limits trip and snagging hazard

PURCHASE PACKAGING

Référence	Carton
71425	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



MO71415

DESCRIPTION

Caract.	Protected loops for durability	Force reduction	< 6 kN
Other caract.	Clearance distance: 6 m	Capacity	User of 100 kg
Weight	2 kg	Breaking strength	> 15 kN
Service life	10 years		
Material	Tubular red polyester webbing width 44mm		
Length	2 m		
Connectors	1 steel screw karabiner and 2 x 50 mm steel scaffold hooks		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **4345 Issue 6 Ext 2**
 Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom



EPI CAT. III

EN355:2002

Energy absorbers