coverguard

TECHNICAL DATASHEET

Ref. MO66795

Welding











The +

2 in 1 : screen shade 4 with automatical adjustment from T9 to T13 Automatic welding of the shade in 1/25 000s Adjustable helmet by rack

Compatible with prescription glasses / breathing masks

PURCHASE PACKAGING

Référence	Taille	Sachet	Carton
66795		0,13	8

SALES PACKAGING

x1

Individual pack

DESCRIPTION

Solar cell / 2 captors, view window size : 98x47mm, low amperage TIG rated 10A, external shade control

APPLICATIONS

Electronic welding, MIG, MAG/CO2, Air carbone, TIG PLASMA

coverguard

DRAGON

Main risk

TECHNICAL FEATURES

Color	Grey
Features	Solar cell - switching time: 1/10.000s - 2 captors - low amperage TIG rate 10A - External shade controle - polyamide / nylon helmet - adjustable headguard
Other features	WELDING HELMET
Weight	435g
Frame	
Lens colour	9 to 13
Shade	9 to 13

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate C5334LUXOPTICAL/R0

Delivered by DIN CERTCO (0196) Alboinstraße 56 12103 BERLIN Germany

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate C5334LUXOPTICAL/R0

Delivered by DIN CERTCO (0196) Alboinstraße 56 12103 BERLIN Germany



EN175:1997

Welding equipments

EN379:2003+A1:2009

Welding filters with variable shade or dual shade

RETAILER STAMP

MAJ 04/03/2021

For further information, please visit www.coverguard-safety.com

COVERGUARD 555 rue de la Dombes, 01700 Miribel - Tél +33 4 72 26 57 57