coverguard®

TECHNICAL DATASHEET
MO71415

Ref. MO71415

Lanyards

Absorbing Lanyards









The +

Elastic webbing reduces length when not in tension and limits trip and snagging hazard

PURCHASE PACKAGING

Référence	Carton
71415	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

* Shock absorbing lanyard designed to limit the forces in the body in the event of a fall
* Connecting element for a fall arrest system

See also

VARIANTS



MO71425

DESCRIPTION

Caract.	Protected loops for durability
Other caract.	Clearance distance: 6 m
Weight	1,1 kg
Service life	10 years
Material	Tubular red polyester webbing width 44mm
Length	2 m
Connectors	1 steel screw karabiner and 1 x 50 mm steel scaffold hook
Force reduction	< 6 kN
Capacity	User of 100 kg
Breaking strength	>15kN

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **6174 Issue 2 Ext 1**
Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom

CE

EPI CAT. III

EN355:2002 Energy absorbers

COVERGUARD
555 rue de la Dombes, 01700 Miribel - Tél +33 4 72 26 57 57