

Lanyards



DESCRIPTION

Caract.	Loops with thimbles	Breaking strength	> 15 kN
Other caract.	Clearance distance: 6 m		
Weight	1,6 kg		
Service life	10 years		
Material	Braided rope Ø 11 mm		
Length	1,8 m		
Connectors	1 steel screw karabiner and 2 x 60 mm aluminium scaffold hooks		
Force reduction	< 6 kN		
Capacity	User of 100 kg		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **4333 Issue 5 Ext 1**
 Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way
 Kettering- Northamptonshire- NN16 8SD United Kingdom



EPI CAT. III

EN355:2002

Energy absorbers

Absorbing Lanyards



The +

Hooks in aluminium for lighter weight

PURCHASE PACKAGING

Référence	Carton
71422	10

SALES PACKAGING

Hangable individual pack

APPLICATIONS

- * Double leg shock absorbing lanyard designed to limit the forces in the body in the event of a fall
- * Provides 100% Tie-Off when the user is required to move from one anchor to another
- * Connecting element for a fall arrest system

See also

VARIANTS



MO71412